

# **Radiation Shielding Studies for the MuCool Test Area at Fermilab**

**Igor Rakhno**

*University of Illinois at Urbana-Champaign*

**ICAR workshop at Argonne National Laboratory**

**May 19-20, 2004**

## Outline

- **Introduction**
- **3D Geometry Model of the MuCool Test Area (MTA)**
- **Proton Beam & Target**
- **Calculated Dose Distributions & Neutron Energy Spectra**
- **Classification**

## Introduction

The MuCool Test Area (MTA) is an intense primary beam facility derived directly from the Fermilab Linac to test heat deposition and other technical concerns associated with the liquid hydrogen targets being developed for cooling intense muon beams.

In this study the results of Monte Carlo radiation shielding calculations performed using MARS14 code are presented and discussed.

The areas taken into account:

- Downstream portion of the target hall and berm around it
- Access pit
- Service building
- Parking lot

Final classification is given for these areas at normal operating conditions according to the Fermilab Radiological Control Manual.


## Introduction - Why MARS?

- **Low-energy neutrons** (below 20 MeV) in MARS are transported with the ENDF/B-VI data by invoking the **MCNP** code. Currently it is a standard in the 'neutron world'.


When working with the **MARS-MCNP** duet, there are two options:

- (i) Invoking MCNP collision physics within MARS;
  - (ii) Generating a source of low-energy neutrons for subsequent MCNP standalone modeling.
- Such **deep-penetration** problems require using an efficient variance reduction technique like **mathematical expectation method** implemented in MARS.


## Geometry Model – Elevation View (Target Hall)



## Geometry Model – Plan View (Lower Level)



## Geometry Model – Plan View (Upper Level)



## Proton Beam & Target

**Beam:** 400-MeV protons;  $\sigma_r = 1\text{ cm}$

$2 \times 10^{14}$  p/s or  $1.3 \times 10^{13}$  p/pulse at 15 Hz repetition rate

### Proton interaction lengths, $\lambda$ (cm)

	<i>LH<sub>2</sub></i>	<i>Al</i>	<i>Cu</i>
$\lambda_{tot}$	910	29	10
$\lambda_{inel}$	1110	41	16

### Targets

<i>Target</i>	<i>L (cm)</i>	<i>R (cm)</i>	<i>% of <math>\lambda_{tot}</math></i>
<i>LH<sub>2</sub></i>	21	10.5	2
<i>Cu</i>	1	10	10



## Proton Beam & Target (2)

*Spallation neutron studies* → full absorption ( $\approx 100\%$ )


targets of heavy & dense materials (Pb, Unat) are used.

- It is claimed that the facility can serve as a multi-purpose one for future operations.
- The 1-cm thick copper target (10% of interaction length) is considered as a generic (modest “averaged”) target.



## Calculated Dose Distributions above the Berm (normal operation)

$$\text{Attenuation} = \exp(-x_1 / \alpha_1 - x_2 / \alpha_2)$$

Material (density, g/cm <sup>3</sup> )	Attenuation length, $\alpha$ (cm)
Compacted soil (2.24)	39
High-density concrete (3.64)	28
Iron (7.87)	23



## Dose Equivalent above the Berm (normal operation)




Calculated shielding compositions which provide the dose level of 0.5 mrem/hr on the top of the MTA shielding.

10.5' of high-density concrete + 2' of dirt (**total is 12.5'**) provide 5 mrem/hr on the top

**Controlled Area** of minimal occupancy (0.25 – 5 mrem/hr, just signs).

## Dose Equivalent above the Berm (normal operation) (2)



At present we have 11' of dirt  $\rightarrow$  330 mrem/hr (10% target).



For a 21-cm LH2 (2% target) it means 66 mrem/hr.

**Radiation Area**  $\rightarrow$  dose rate from 5 up to 100 mrem/hr (Fermi RCM).

## Calculated Dose Distributions in the Access Pit (normal operation)


Lower Level

Upper Level




## Dose Equivalent in the Cryo Room (normal operation)

### 10" penetration




### 4" and 8" penetrations




## Neutron Energy Spectra in the 10" Penetration (normal operation)

Near target hall



Near cryo room



## Three options for additional shielding

### 1. A wall in target hall in front of penetrations.

$$H \times W \times T = (200 + 95) \text{ cm} \times 80 \text{ cm} \times 10 \text{ cm}$$

↓   ↓

*BMCN   Tungsten*

↓   ↓

600 kg   1500 kg

### 2. A wall instead of the door between cryo room & compressor room.

$$H \times W \times T = 220 \text{ cm} \times 190 \text{ cm} \times 20 \text{ cm}$$


Regular concrete  $\approx$  2000 kg.

### 3. Two 2'' iron collimators, 20'' in length, inside the 10'' penetration.

Two 1'' iron collimators, 20'' in length, inside the 8'' penetration.




## Dose Distribution in the Service Building for the 3 shielding options



To reduce dose at the parking lot, both 2<sup>nd</sup> and 3<sup>rd</sup> option are more efficient when compared to the 1<sup>st</sup> one.

## Dose Distribution in the Service Building (options 2 and 3 together)




To reduce further the dose at parking lot, additional local shielding is required  
near the internal wall in the refrigerator room.

A 50-cm iron block  $\Rightarrow$  the predicted dose at parking lot  $\leq$  0.05 mrem/hr  
at normal operation at  $10^{14}$  p/s.

## Conclusions

1. A credible beam accident at MTA is less severe than normal operation.
2. At normal operation the following classification is suggested (Fermi RCM):
  - Berm above target hall – **Controlled Area** of minimal occupancy (0.25 – 5 mrem/hr);
  - Access pit – **Radiation Area** with rigid barriers/locked gates (5 – 100 mrem/hr);
  - Cryo room - **Radiation Area** with rigid barriers/locked gates (5 – 100 mrem/hr);
  - Compressor room - **Controlled Area** of minimal occupancy (0.25 – 5 mrem/hr);
  - Parking lot – **Normal area** of unlimited occupancy (dose rate  $\leq 0.05$  mrem/hr).

## Quality of the calculations – NuMI Activation Experiment (2000-2001)



**AP0 Enclosure  
at Fermilab**

## Quality of the calculations – NuMI Activation Experiment (2000-2001)

